

36"-HIGH LOCKING BAR HANDLES

Make it easy to leverage your body weight to open or close the container doors, compared to standard 20"H locking bar handles.

CORTEN STEEL

Known for its unique rust-inhibitive properties, it gives containers durability and resistance to the elements.

SECURE LOCKBOX

Features a thick metal casing to protect the padlock from bolt cutters and other break-in tools.

FRONT ACCESS DOOR

The front of the container is accessible through one (1) container barn door with standard locking bar handle and lockbox.

DOOR SEALS

Built with 2-stage EPDM rubber which is water and weather resistant from -100°C to +300°C.



WEATHERPROOF VENTS

Help reduce heat, humidity and prevent condensation from forming.

PAINT

All our new shipping containers are painted with low VOC, water-based paint and zinc-enriched primer to ensure maximum resistance to the elements.

OEM DOORS

A second set of OEM doors is installed at the manufacturer, opposite the original container doors. This second set of doors facilitates loading/unloading and provides additional secure access to the container. These doors include an additional secure lockbox.

FORKLIFT POCKETS

Facilitate easy loading and unloading.

MARINE GRADE FLOORING

Consists of 1.1" thick, 19-ply marine grade plywood that can support up to 62,130lbs of payload and is treated to withstand spills and other contaminants.

WEIGHT & DIMENSIONS

Exterior: 20'L x 8'W x 8'6"H
Interior: 19'6"L x 7'8"W x 7'10"H
Door Opening: 7'8"W x 7'5"H

Forklift pockets: 14"W x 4"H
Fork spread: 82"W center to center

Weight: 5,070 LBS
Payload: 62,130 LBS

MODIFICATION OPTIONS




Paint Decals Rollup Doors Garage Doors



Ventilation Man Doors Windows Insulation

CONTAINER ACCESSORIES



Lockbox Padlock Puck lockbox Stacking pin



Pipe Storage Insta Vents Shelving Deck Mount