





Help reduce heat, humidity and prevent condensation from forming.

PAINT

All our new shipping containers are painted with low VOC, water-based paint and zinc-enriched primer to ensure maximum resistance to the elements.

CORTEN STEEL

Known for its unique rust-inhibitive properties, it gives containers durability and resistance to the elements.

MARINE GRADE FLOORING

Consists of 1.1" thick, 19-ply marine grade plywood that can support up to 10,980lbs of payload and is treated to withstand spills and other contaminants.

WEIGHT & DIMENSIONS

Exterior: 9'L x 7'2"W x 7'5"H Interior: 8'6"L x 6'11"W x 6'9"H Door Opening: 6'10"W x 6'7"H

Forklift pockets: 12.5"W x 4"H Fork spread: 35.5"W center to center

Weight: 2,250 LBS Payload: 10,980 LBS



SECURE LOCKBOX

ATSU 098103 8

1000 652 15.65 28 1.000 652 2.210 05 1.000 653 11.25 10.0 11.1 00.0 400 00.7

MAX.GR.

Features a thick metal casing to protect the padlock from bolt cutters and other break-in tools.

DOOR SEALS

Built with 2-stage EPDM rubber which is water and weather resistant from -100°C to +300°C.

36"-HIGH LOCKING BAR HANDLES

Make it easy to leverage your body weight to open or close the container doors, compared to standard 20"H locking bar handles.

CSC PLATE

The CSC Safety approval plate guarantees that the container meets international safety standards and transport certifications.

FORKLIFT POCKETS


Facilitate easy loading and unloading.

CONTAINER ACCESSORIES









Shelving



Deck Mount

MODIFICATION OPTIONS